

View Online at <https://aerobasegroup.com/nsn/5905-01-338-8124>

**Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-30.0/+30.0

**Electrical Resistance:**

3.300 kilohms

**Resistance Tolerance In Percent:**

-1.000/+1.000

**Ambient Temperature In Deg Celsius At Full Rated Power:**

25.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

275.0

**Temperature Range Of Temperature Coefficient In Deg Celsius:**

-55.0/+275.0

**Inclosure Method:**

Encapsulated

**Terminal Type:**

Threaded stud

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.958 inches and 1.020 inches

**Body Length:**

Between 3.406 inches and 3.594 inches

**Body Width:**

Between 1.781 inches and 1.843 inches

**Body Height:**

Between 1.719 inches and 1.781 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.740 inches and 2.760 inches

**Power Dissipation Rating In Watts:**

30.000 free air

**End Application:**

4920-01-187-4068 test system, aut

**Mounting Hole Size:**

Between 0.178 inches and 0.198 inches

**Cubic Measure (non-core):**

11.797 cubic inches

**Unpackaged Unit Weight:**

400.0 grams

**Style Designator:**

Axial terminal (s)

**Test Data Document:**

81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-r-18546/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A001a0