

View Online at https://aerobasegroup.com/nsn/5905-01-338-8139

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Shaft Diameter:

0.044 inches

Shaft Length:

0.060 inches

Body Length:

0.375 inches

Body Width:

0.202 inches

Body Height:

0.395 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Fragility Factor:

Moderately rugged

End Application:

Radar test se

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Features Provided:

Humidity proof

Cubic Measure:

0.029 cubic inches

Electrical Resistance Per Section:

1.0 percent, rated amperes c and better flooring

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

NSN 5905-01-338-8139 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Specification Data:

28480-2100-4090 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0