

View Online at <https://aerobasegroup.com/nsn/5905-01-339-0193>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.500 inches

Shaft Diameter:

Between 0.124 inches and 0.126 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.469 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

270.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Maximum Stop Torque:

48.00 inch-ounces

Nonturn Device Location:

At 4'30 oclock and at 10'30 oclock

Nonturn Device Radius:

Between 0.240 inches and 0.250 inches

Fragility Factor:

Moderately rugged

End Application:

6625-01-224-4440 network analyzer

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Hermetically sealed and humidity proof and panel seal

Cubic Measure:

0.092 cubic inches

Electrical Resistance Per Section:

500.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 290.0 and 300.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+8.0 -55 degrees celsius single section and +0.0/+4.0 -25 degrees celsius single section and +0.0/+2.0 0 degrees celsius single section and -3.0/+3.0 85 degrees celsius single section and +0.0/+6.0 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

Immersion sealed

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

28480-2100-3763 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0