NSN 5905-01-339-1393

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-339-1393

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -50.0/+50.0 Electrical Resistance: 47.000 kilohms Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches Schematic Diagram Designator:
Electrical Resistance: 47.000 kilohms Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
47.000 kilohms Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
-2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
-55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Inclosure Method: Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Encapsulated Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Terminal Quantity: 9 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Tab, solder lug Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Reliability Indicator: Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Not established Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Terminal Length: Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Between 0.125 inches and 0.150 inches Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Body Length: 0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
0.898 inches Body Width: 0.098 inches Body Height: 0.200 inches
Body Width: 0.098 inches Body Height: 0.200 inches
0.098 inches Body Height: 0.200 inches
Body Height: 0.200 inches
0.200 inches
Conomictor Blagram Beorginator.
Ladder network
Power Dissipation Rating In Watts:
0.300 total network
Terminal Width:
Between 0.018 inches and 0.022 inches
Identical Value Resistor Quantity:
8 each resistor
Style Designator:
Single inline
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5905-01-339-1393

Film Fixed Resistor Network - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0