NSN 5905-01-339-8414

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-339-8414

1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Shaft Diameter:
0.125 inches
Shaft Length:
0.031 inches
Body Length:
12.300 inches
Body Width:
12.700 inches
Body Height:
12.700 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
295.0
Maximum Stop Torque:
3.00 inch-ounces
Center To Center Distance Between Terminals:
0.100 inches
Screw Thread Series Designator:
Unef
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section

NSN 5905-01-339-8414

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0