## NSN 5905-01-339-9020

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-339-9020 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.625 inches Flat Height: Between 0.214 inches and 0.218 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** Between 0.571 inches and 0.633 inches **Body Width:** 0.625 inches **Body Height:** 0.725 inches **Shaft Style:** Round, flatted Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 23.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Maximum Stop Torque:** 64.00 inch-ounces

Nonturn Device Location: At 9 oclock

Nonturn Device Radius:

0.305 inches

## NSN 5905-01-339-9020

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Double pole, single throw, one open, one closed
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Right-left adjacent sides
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
2.000 ac
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
7 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5905-01-339-9020

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0