NSN 5905-01-340-7378

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-340-7378

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.187 inches
Shaft Diameter:
0.078 inches
Shaft Length:
0.040 inches
Body Length:
0.312 inches
Body Width:
0.190 inches
Body Height:
0.312 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
5400.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Cubic Measure:
0.018 cubic inches
Electrical Resistance Per Section:
200.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

NSN 5905-01-340-7378

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:** -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.3 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure: Demilitarization:**