Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-340-9048

New Online at https://aerobasegroup.com/hsr/3303-01-340-3040
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
2.000 inches
Shaft Diameter:
Between 0.2495 inches and 0.2498 inches
Shaft Length:
0.375 inches
Mounting Bushing Length:
0.312 inches
Body Length:
0.969 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
270.0
Maximum Starting Torque:
96.00 inch-ounces
Maximum Running Torque:
32.00 inch-ounces
Maximum Stop Torque:
80.00 inch-ounces
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.005 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches



Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

#### Mounting Method:

Standard bushing

#### **Cubic Measure:**

3.044 cubic inches

**Electrical Resistance Per Section:** 

1.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

270.0

Function Conformity Tolerance Per Section:

-0.30/+0.30 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

**Power Dissipation Rating Per Section In Watts:** 

4.0 free air single section

**Function Conformity Per Section:** 

Single section independent linearity

**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

#### Actuator Travel Control Feature:

Stops

**Function Characteristic Per Section:** 

Single section linear

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

## Precious Material And Location:

Terminal surfaces gold and contact surfaces silver

## Precious Material:

Gold and silver

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

# NSN 5905-01-340-9048

Precision Wire Wound Variable Resistor - Page 3 of 3

Fiig: A002a0

