## NSN 5905-01-341-3063

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-341-3063 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.160 inches **Shaft Diameter:** 0.100 inches **Shaft Length:** 0.310 inches **Body Length:** 0.750 inches **Body Width:** 0.160 inches **Body Height:** 0.310 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 5400.0 **Center To Center Distance Between Terminals:** 0.500 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Lower adjacent side two rows **Mounting Method: Terminal Center To Center Distance Between Terminal Rows:** 0.100 inches **Features Provided:** Shaft seal **Cubic Measure:** 

0.037 cubic inchesElectrical Resistance Per Section:2.0 kilohms single section

## NSN 5905-01-341-3063

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
5400.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.200 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Specification Data:
94697-a05637 manufacturers specification control
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A002a0