NSN 5905-01-341-6702

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-341-6702

| view Online at https://aerobasegroup.com/hsh/0300-01-041-0702 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -100.0/+100.0 |
| Electrical Resistance: |
| 16.000 kilohms |
| Resistance Tolerance In Percent: |
| -2.000/+2.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 14 |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.105 inches and 0.215 inches |
| Body Length: |
| Between 0.695 inches and 0.785 inches |
| Body Width: |
| Between 0.240 inches and 0.305 inches |
| Body Height: |
| 0.180 inches |
| Schematic Diagram Designator: |
| Isolated array |
| Power Dissipation Rating In Watts: |
| 1.400 total network |
| Identical Value Resistor Quantity: |
| 7 each resistor |
| Style Designator: |
| Dual inline |
| Test Data Document: |
| 81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-r-83401/1 government specification |

N/a

Shelf Life:

NSN 5905-01-341-6702

Film Fixed Resistor Network - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A001a0