

View Online at <https://aerobasegroup.com/nsn/5905-01-341-7921>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

1.655 inches

**Shaft Diameter:**

0.250 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.812 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

320.0

**Maximum Starting Torque:**

0.50 inch-ounces

**Maximum Running Torque:**

0.30 inch-ounces

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Radially positioned over less than half the circumference

**Features Provided:**

Humidity proof

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Power Dissipation Rating Per Section In Watts:**

6.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Function Characteristic Per Section:**

Single section linear

**Terminal Type And Quantity:**

4 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0