Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-341-8894

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

Electrical Resistance:

390.000 kilohms

Resistance Tolerance In Percent:

-2.000/+2.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

- Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
- 125.0
- Tempurature Range Of Tempurature Coefficient In Deg Celsius:
- -55.0/+125.0
- **Inclosure Method:**
- Encapsulated
- **Terminal Quantity:**
- 14
- Terminal Type:
- Tab, solder lug
- Reliability Indicator:
- Not established
- Terminal Length:
- Between 0.105 inches and 0.215 inches
- **Body Length:**
- Between 0.695 inches and 0.785 inches
- **Body Width:**
- Between 0.240 inches and 0.305 inches
- **Body Height:**
- 0.180 inches
- Schematic Diagram Designator:
- Ladder network
- **Power Dissipation Rating In Watts:**
- 1.300 total network
- Terminal Width:
- Between 0.015 inches and 0.022 inches
- **End Application:**
- 4920-01-203-1835 test station, electrical
- Identical Value Resistor Quantity:
- 13 each resistor
- Style Designator:
- Dual inline

Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Film Fixed Resistor Network - Page 2 of 2



Specification Data:

81349-mil-r-83401/1 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0