NSN 5905-01-342-2666

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-342-2666

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -100.0 to 100.0 Electrical Resistance: 3.010 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 225.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 230.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Electrical Resistance: 3.010 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 225.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 230.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
3.010 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 225.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 230.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Resistance Tolerance In Percent: -1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 225.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 230.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
-1.000 to 1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 225.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 230.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 225.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 230.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 225.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 230.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 225.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 230.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 230.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0 to 230.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
-65.0 to 230.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Between 1.375 inches and 1.625 inches Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Body Diameter: Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Between 0.082 inches and 0.098 inches Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Body Length: Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Between 0.220 inches and 0.260 inches Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Power Dissipation Rating In Watts: 1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
1.000 free air Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
Unpackaged Unit Weight: 0.2 grams Style Designator: Axial terminal each end Shelf Life:
0.2 grams Style Designator: Axial terminal each end Shelf Life:
Style Designator: Axial terminal each end Shelf Life:
Axial terminal each end Shelf Life:
Shelf Life:
N1/-
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A004-0
A001a0