NSN 5905-01-342-4479

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-342-4479

| view Online at https://aerobasegroup.com/hsn/5905-01-342-4479 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -100.0/+100.0 |
| Electrical Resistance: |
| 220.000 kilohms |
| Resistance Tolerance In Percent: |
| -5.000/+5.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 14 |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.105 inches and 0.215 inches |
| Body Length: |
| Between 0.695 inches and 0.785 inches |
| Body Width: |
| Between 0.240 inches and 0.305 inches |
| Body Height: |
| 0.180 inches |
| Schematic Diagram Designator: |
| Ladder network |
| Power Dissipation Rating In Watts: |
| 1.300 total network |
| Terminal Width: |
| Between 0.015 inches and 0.022 inches |
| Identical Value Resistor Quantity: |
| 13 each resistor |
| Style Designator: |
| Dual inline |
| Test Data Document: |
| 81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-83401/1 government specification

NSN 5905-01-342-4479

Film Fixed Resistor Network - Page 2 of 2



| _ | | | | | |
|---|----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0