NSN 5905-01-342-9427

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-342-9427

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
0.172 inches
Body Length:
0.250 inches
Body Width:
Between 0.230 inches and 0.270 inches
Body Height:
Between 0.230 inches and 0.270 inches
Actuator Type:
Flush drive with slot-hole
Center To Center Distance Between Terminals:
1.000 inches
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
10.0 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
1.000 inches
Power Dissipation Rating Per Section In Watts:
0.250 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Test Data Document:
81349-mil-r-39035b specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Specification Data:
81349-mil-r-39035/4d government specification
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5905-01-342-9427

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0