NSN 5905-01-344-4602

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-344-4602

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|---|
| -200.0/+200.0 |
| Electrical Resistance: |
| 100.000 ohms20.000 kilohms464.000 ohms954.000 ohms |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 16 |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.125 inches and 0.150 inches |
| Body Length: |
| Between 0.784 inches and 0.876 inches |
| Body Width: |
| Between 0.240 inches and 0.305 inches |
| Body Height: |
| 0.200 inches |
| Schematic Diagram Designator: |
| Ladder network |
| Power Dissipation Rating In Watts: |
| 1.500 total network |
| Terminal Width: |
| Between 0.015 inches and 0.022 inches |
| Identical Value Resistor Quantity: |
| 4 lowest resistance value4 highest resistance value2 1st intermediate resistance value4 2nd intermediate resistance value |
| Style Designator: |
| Dual inline |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5905-01-344-4602

Film Fixed Resistor Network - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0