Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-346-1558

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

#### **Electrical Resistance:**

49.900 kilohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

## Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

#### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

**Inclosure Method:** 

Encapsulated

#### **Terminal Quantity:**

16

#### Terminal Type:

Tab, solder lug

# Reliability Indicator:

Not established

### Terminal Length:

Between 0.105 inches and 0.215 inches

#### **Body Length:**

Between 0.784 inches and 0.876 inches

#### **Body Width:**

Between 0.240 inches and 0.305 inches

#### **Body Height:**

0.180 inches

#### Schematic Diagram Designator:

Isolated array

#### **Power Dissipation Rating In Watts:**

1.600 total network

#### **Terminal Width:**

Between 0.010 inches and 0.015 inches

## Identical Value Resistor Quantity:

8 each resistor

# **Special Features:**

Nuclear hardness critical items

# **Nuclear Hardness Critical Feature:**

Hardened

# Style Designator:

Dual inline

# NSN 5905-01-346-1558

Film Fixed Resistor Network - Page 2 of 2



#### **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-r-83401/2 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0