NSN 5905-01-347-8753

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-347-8753

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.750 inches
Body Length:
0.287 inches
Body Width:
0.276 inches
Body Height:
0.339 inches
Actuator Type:
Flush drive with slot-hole
Center To Center Distance Between Terminals:
Between 0.090 inches and 0.110 inches
End Application:
G662-50-127-9344
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
1.0 megohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.185 inches and 0.215 inches
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Continuous motion
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a

NSN 5905-01-347-8753

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0