Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-347-8753

Section	Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

- **Terminal Length:**
- 0.750 inches

Body Length:

0.287 inches

Body Width:

0.276 inches

Body Height:

0.339 inches

Actuator Type:

Flush drive with slot-hole

Center To Center Distance Between Terminals:

Between 0.090 inches and 0.110 inches

End Application:

G662-50-127-9344

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Electrical Resistance Per Section:

1.0 megohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

Between 0.185 inches and 0.215 inches

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0