NSN 5905-01-348-9959

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-348-9959

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Cylindrical |
| Reliability Indicator: |
| Not established |
| |
| Body Diameter: 0.305 inches |
| 51535 MB/ISC |
| Body Length: |
| 0.255 inches |
| Shaft Bearing Type: |
| Sleeve |
| Actuator Type: |
| Flush drive with slot-hole |
| Maximum Starting Torque: |
| 5.00 inch-ounces |
| Maximum Running Torque: |
| 5.00 inch-ounces |
| Maximum Stop Torque: |
| 5.00 inch-ounces |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Terminal |
| Electrical Resistance Per Section: |
| 1.0 kilohms single section |
| Function Conformity Tolerance Per Section: |
| -10.00/+10.00 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 0.5 free air single section |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Function Characteristic Per Section: |
| Single section linear |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 85.0 single section |
| Terminal Type And Quantity: |
| 3 wire lead |

NSN 5905-01-348-9959

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A002a0