# NSN 5905-01-349-5573

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-349-5573

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-5.0/+5.0 first temp coefficient-10.0/+10.0 second temp coefficient

# **Electrical Resistance:**

88.700 ohms

**Resistance Tolerance In Percent:** 

-0.100/+0.100

# Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

# Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0 temp range of first temp coefficient+125.0/+175.0 temp range of second temp coefficient

#### **Inclosure Method:**

Encapsulated

**Terminal Type:** 

Wire lead

Mil-std-1276 Wire Lead Type Designator:

С

**Reliability Indicator:** 

Established

Reliability Failure Rate Level In Percent:

0.010

## **Terminal Length:**

Between 0.875 inches and 1.875 inches

#### **Body Length:**

Between 0.290 inches and 0.320 inches

#### **Body Width:**

0.336 inches

**Body Height:** 

Between 0.095 inches and 0.120 inches

#### **Power Dissipation Rating In Watts:**

0.300 free air

Cubic Measure (non-core):

0.013 cubic inches

# Style Designator:

Terminals one edge

## **Test Data Document:**

81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-55182/9 government specification

# Shelf Life:

N/a

# NSN 5905-01-349-5573

Film Fixed Resistor - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0

