## NSN 5905-01-350-1950

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-350-1950
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0 to 100.0
Electrical Resistance:
649.000 kilohms
Resistance Tolerance In Percent:
-1.000 to 1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0 to 150.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Mil-std-1276 Wire Lead Type Designator:
C
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
Between 1.000 inches and 1.625 inches
Body Diameter:
Between 0.058 inches and 0.074 inches
Body Length:
Between 0.130 inches and 0.170 inches
Power Dissipation Rating In Watts:
0.125 free air
Unpackaged Unit Weight:
0.3 grams
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39017/5 government specification
Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5905-01-350-1950

Film Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0