Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-351-3649

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.3740 inches and 0.3750 inches

Pilot Length:

0.0620 inches

First Flat Length:

0.210 inches

Undercut Diameter:

0.400 inches

Undercut Width:

0.0630 inches

Body Diameter:

0.515 inches

Angle Of Mounting Hole In Deg:

120.0

Angle Between Centerlines Of Mounting Holes In Deg:

120.0

Shaft Diameter:

0.093 inches

Shaft Length:

0.688 inches

Body Length:

1.188 inches

Mounting Lip Diameter:

0.5150 inches

Mounting Lip Depth:

0.0620 inches

Mounting Hole/stud Circle Diameter:

Between 0.374 inches and 0.375 inches

Shaft Style:

Round, v flatted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 3240.0 and 3260.0



Maximum Starting Torque: 0.50 inch-ounces Maximum Running Torque: 0.30 inch-ounces **Maximum Stop Torque:** 20.00 inch-ounces Mechanical Backlash In Deg Angular Rotation: 0.1 **Terminal Location:** Rear end **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 10.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 3240.0 and 3260.0 **Function Conformity Tolerance Per Section:** -0.15/+0.15 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -200.0/+200.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Function Conformity Per Section:** Single section absolute linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -55.0/+125.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 20.0 single section **Terminal Type And Quantity:** 3 solder stud Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

NSN 5905-01-351-3649

Precision Wire Wound Variable Resistor - Page 3 of 3

Fiig: A002a0

