Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-351-5508

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0/+50.0

#### **Electrical Resistance:**

1.000 kilohms

**Resistance Tolerance In Percent:** 

-2.000/+2.000

## Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

Encapsulated

## **Terminal Quantity:**

8

## **Terminal Type:**

Tab, solder lug

# Reliability Indicator:

Not established

## Terminal Length:

Between 0.105 inches and 0.215 inches

## **Body Length:**

Between 0.784 inches and 0.876 inches

#### **Body Width:**

Between 0.240 inches and 0.305 inches

## **Body Height:**

0.180 inches

Schematic Diagram Designator:

Isolated array

## **Power Dissipation Rating In Watts:**

2.400 total network

## Terminal Width:

Between 0.015 inches and 0.022 inches

## Identical Value Resistor Quantity:

8 each resistor

# Style Designator:

Single inline

## **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-83401/2 government specification

Film Fixed Resistor Network - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0

