

View Online at <https://aerobasegroup.com/nsn/5905-01-353-5309>

Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

Electrical Resistance:

240.000 ohms

Resistance Tolerance In Percent:

-1.000/+1.000

Ambient Temperature In Deg Celsius At Full Rated Power:

70.0

Ambient Temperature In Deg Celsius At Zero Percent Rated Power:

150.0

Temperature Range Of Temperature Coefficient In Deg Celsius:

-55.0/+150.0

Inclosure Method:

Encapsulated

Terminal Type:

Wire lead

Mil-std-1276 Wire Lead Type Designator:

C

Reliability Indicator:

Not established

Terminal Length:

Between 1.375 inches and 1.625 inches

Body Diameter:

Between 0.250 inches and 0.593 inches

Body Length:

0.562 inches

Power Dissipation Rating In Watts:

1.000 free air

End Application:

Narleigh burke class ddg; ticonderoga class cg (47); nimitz class cvn; wasp class lhd; forrestal class cv; emory s. Land class as; tarawa class lha; 2m/ate microminiature automatic test equipment; avenger class mcm

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Style Designator:

Axial terminal each end

Test Data Document:

81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-39017/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A001a0