## NSN 5905-01-354-0876

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-354-0876

## **Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-1.000/+1.000 first temp coefficient

**Electrical Resistance:** 

221.000 kilohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0/+125.0 temp range of first temp coefficient

**Inclosure Method:** 

Encapsulated

**Terminal Quantity:** 

10

**Terminal Type:** 

Pin

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 0.125 inches and 0.150 inches

**Body Length:** 

Between 0.968 inches and 0.998 inches

**Body Width:** 

Between 0.332 inches and 0.352 inches

**Body Height:** 

Between 0.050 inches and 0.103 inches

**Schematic Diagram Designator:** 

Ladder network

**Power Dissipation Rating In Watts:** 

1.800 total network

**Identical Value Resistor Quantity:** 

9 each resistor

**Style Designator:** 

Single inline

## Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-r-83401/6 government specification

Shelf Life:

N/a

## NSN 5905-01-354-0876

Film Fixed Resistor Network - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A001a0