NSN 5905-01-356-1328

Inductive Wire Wound Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-356-1328 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -50.0/+50.0 |
| Electrical Resistance: |
| 3.160 ohms |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 275.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+275.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Threaded stud |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.958 inches and 1.020 inches |
| Body Length: |
| Between 3.406 inches and 3.594 inches |
| Body Width: |
| Between 1.781 inches and 1.843 inches |
| Body Height: |
| Between 1.719 inches and 1.781 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| Between 2.990 inches and 3.010 inches |
| Power Dissipation Rating In Watts: |
| 30.000 free air |
| Mounting Hole Size: |
| Between 0.178 inches and 0.198 inches |
| Style Designator: |
| Axial terminal (s) |
| Test Data Document: |
| 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |

Specification Data:

81349-mil-r-18546/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5905-01-356-1328

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0