Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-356-8401

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Body Length:

0.110 inches

Body Width:

0.205 inches

Body Height:

0.250 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

210.0

Maximum Starting Torque:

3.50 inch-ounces

Maximum Running Torque:

3.50 inch-ounces

Maximum Stop Torque:

300.00 centimeter-grams

Fragility Factor:

Moderately rugged

Terminal Location:

Rear end

Mounting Method:

Snap-in

Features Provided:

Humidity proof

Electrical Resistance Per Section:

10.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

240.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-250.0/+250.0 single section

Power Dissipation Rating Per Section In Watts:

0.1 7th secondary quality

Resistance Tolerance Per Section In Percent:

-25.0/+25.0 single section

NSN 5905-01-356-8401

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0