# NSN 5905-01-359-1950

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-359-1950

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

**Electrical Resistance:** 

68.000 ohms

**Resistance Tolerance In Percent:** 

-2.000/+2.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+150.0

**Inclosure Method:** 

Encapsulated

**Terminal Type:** 

Wire lead

Mil-std-1276 Wire Lead Type Designator:

С

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.001

Terminal Length:

Between 1.375 inches and 1.625 inches

### **Body Diameter:**

Between 0.175 inches and 0.205 inches

### Body Length:

Between 0.520 inches and 0.593 inches

### **Power Dissipation Rating In Watts:**

1.000 free air

### **End Application:**

Avenger class mcm; an/sqq-32 mine hunting sonar set; missile, minuteman lgm-30; aircraft, b-2 bomber (atb); missile, patriot; osprey class mhc

**Criticality Code Justification:** 

Feat

**Special Features:** 

Weapon system essential

#### Style Designator:

Axial terminal each end

## **Test Data Document:**

81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

813/19-mil-r-30017/2 government specification

# NSN 5905-01-359-1950

Film Fixed Resistor - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0

