## NSN 5905-01-359-1950

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-359-1950
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
68.000 ohms
Resistance Tolerance In Percent:
-2.000/+2.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+150.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Mil-std-1276 Wire Lead Type Designator:
C
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
Between 1.375 inches and 1.625 inches
Body Diameter:
Between 0.175 inches and 0.205 inches
Body Length:
Between 0.520 inches and 0.593 inches
Power Dissipation Rating In Watts:
1.000 free air
End Application:
Avenger class mcm; an/sqq-32 mine hunting sonar set; missile, minuteman lgm-30; aircraft, b-2 bomber (atb); missile, patriot; osprey
class mhc
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Style Designator:
Axial terminal each end
Test Data Document:

81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Specification Data:

813/10-mil-r-30017/2 government enecification

## NSN 5905-01-359-1950

Film Fixed Resistor - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0