## NSN 5905-01-360-3949

Film Fixed Resistor Network - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5905-01-360-3949
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-50.0/+50.0
Electrical Resistance:
2.000 kilohms
Resistance Tolerance In Percent:
-0.100/+0.100
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
8
Terminal Type:
Pin
Reliability Indicator:
Not established
Terminal Length:
Between 0.125 inches and 0.150 inches
Body Length:
Between 0.768 inches and 0.798 inches
Body Width:
Between 0.050 inches and 0.103 inches
Body Height:
Between 0.177 inches and 0.197 inches
Schematic Diagram Designator:
Isolated array
Power Dissipation Rating In Watts:
0.480 total network
Identical Value Resistor Quantity:
4 each resistor
Style Designator:
Single inline
Test Data Document:
81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-83401/8 government specification

N/a

Shelf Life:

## NSN 5905-01-360-3949

Film Fixed Resistor Network - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A001a0