NSN 5905-01-360-3955

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-360-3955

| Section Quantity: |
|-----------------------------------------------------------------------------|
| 1 |
| Body Style: |
| Rectangular bushing mounted |
| Reliability Indicator: |
| Not established |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 1.000 inches |
| Mounting Bushing Length: |
| 0.375 inches |
| Body Length: |
| Between 0.562 inches and 0.624 inches |
| Body Width: |
| 0.625 inches |
| Body Height: |
| 0.625 inches |
| Shaft Style: |
| Round |
| Actuator Type: |
| Single shaft |
| Nonturn Device Location: |
| At 9 oclock |
| Nonturn Device Radius: |
| 0.305 inches |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Lower adjacent side single row |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 1.0 kilohms single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 120.0 single section |
| Power Dissipation Rating Per Section In Watts: |

1.0 free air single section

NSN 5905-01-360-3955

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0