## NSN 5905-01-360-3957

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-01-360-3957



**Section Quantity:** 2 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** Between 0.981 inches and 1.075 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.305 inches **Undercut Length:** 1.375 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Standard bushing

**Electrical Resistance Per Section:** 

1.0 kilohms all sections

## NSN 5905-01-360-3957

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Amhiant "	Tempurature I	n Dag Cal	leiue Par	Section A	At Zero	Parcent	Rated F	Ower.
Allibielli	i eiiiburature i	n Dea Ce	isius rei	Section A	AL ZEIO	rercent	Raieu r	owei.

150.0 all sections

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air all sections

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

**Standard Taper Curve Per Section:** 

A all sections

**Terminal Type And Quantity:** 

6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0