Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-360-4822

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

## **Body Diameter:**

2.000 inches

### Shaft Diameter:

0.249 inches

#### Shaft Length:

0.750 inches

## Mounting Bushing Length:

0.250 inches

### Body Length:

## 1.040 inches

Shaft Style:

Round

## Actuator Type:

Single shaft

## Maximum Starting Torque:

2.00 inch-ounces

## Screw Thread Diameter:

0.375 inches

### Screw Thread Series Designator:

Unf

### Screw Thready Qty Per Inch (tpi):

32.0

### **Terminal Location:**

Radially positioned over more than half the circumference

### **Mounting Method:**

Standard bushing

### **Electrical Resistance Per Section:**

10.0 kilohms single section

### Power Dissipation Rating Per Section In Watts:

4.0 free air single section

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

## **Terminal Type And Quantity:**

6 turret

#### Shelf Life:

N/a

# NSN 5905-01-360-4822

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0