NSN 5905-01-361-6258

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-361-6258

5.0145.0 Electrical Resistance: 9.000 kilohms Resistance Tolerance in Percent: -0.100/40.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inchos Body Length: 8.000 inchos Body Diameter: 8.000 enchos Body Length: 9.000 enchos Body Leng	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
8-900 kilohms Resistance Tolerance in Percent: -0.100/40.100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Diameter: Between 0.078 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Notal Unit of Measure:	-5.0/+5.0
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Length: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: Axial terminal each end Test Data Document: Shelf Life: N/a Unit Of Measure:	Electrical Resistance:
-0.100/40.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Diameter: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure:	9.900 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diamete: Between 0.078 inches and 0.108 inches Body Diamete: Between 0.375 inches and 0.437 inches Power Dissipation Rating in Watts: 0.300 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Diameter: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-e11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: — Demilitarization: No Filg:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Diameter: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Botween 0.078 inches and 0.108 inches Body Diameter: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Diameter: Between 0.078 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-011620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Diameter: Between 0.375 inches and 0.437 inches Power Dissipation Rating in Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	150.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Length: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Length: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a Unit Of Measure: Demilitarization: No Flig:	-55.0/+150.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Length: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Length: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Length: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note stablished Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Length: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Wire lead
Terminal Length: 1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Length: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 0.4274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
1.500 inches Body Diameter: Between 0.078 inches and 0.108 inches Body Length: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Between 0.078 inches and 0.108 inches Body Length: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
Between 0.078 inches and 0.108 inches Body Length: Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.500 inches
Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
Between 0.375 inches and 0.437 inches Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.078 inches and 0.108 inches
Power Dissipation Rating In Watts: 0.500 free air Style Designator: Axial terminal each end Test Data Document: 0.4274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
O.500 free air Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.375 inches and 0.437 inches
Style Designator: Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.500 free air
Test Data Document: 04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	04274-c11620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0