

View Online at <https://aerobasegroup.com/nsn/5905-01-361-6262>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.440 inches

Flat Height:

0.216 inches

Body Diameter:

1.800 inches

Shaft Diameter:

Between 0.250 inches and 0.251 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.380 inches

Body Length:

1.750 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Sleeve

Switch Type:

Pull

Switch Voltage Rating In Volts:

28.0

Actuator Type:

Single shaft

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.500 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Double pole, single throw, normally closed

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.380 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Humidity proof and switch

Switch Current Type And Rating In Amps:

4.000 dc

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0