

View Online at <https://aerobasegroup.com/nsn/5905-01-365-3554>

**Electrical Resistance:**

12.000 kilohms

**Resistance Tolerance In Percent:**

-2.000/+2.000

**Ambient Temperature In Deg Celsius At Full Rated Power:**

70.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

150.0

**Inclosure Method:**

Encapsulated

**Terminal Type:**

Wire lead

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.001

**Body Diameter:**

Between 0.175 inches and 0.205 inches

**Body Length:**

Between 0.520 inches and 0.593 inches

**Power Dissipation Rating In Watts:**

1.000 free air

**End Application:**

Radiation control unit, c5572/s, westinghouse canada inc; oliver perry class ffg; nimitz class cvn; radar set lt air traffic control (17m jul 83) (an/tps-63); teletype, model 28; wasp class lhd; forrestal class cv; arleigh burke class ddg; spruance class dd (963); ticonderoga class cg (47)

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Style Designator:**

Axial terminal each end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A001a0