

View Online at <https://aerobasegroup.com/nsn/5905-01-365-5864>

Section Quantity:

2

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

First Flat Length:

Between 0.303 inches and 0.323 inches

Flat Height:

Between 0.092 inches and 0.096 inches

Shaft Diameter:

Between 0.124 inches and 0.126 inches

Shaft Length:

Between 1.209 inches and 1.229 inches

Mounting Bushing Length:

Between 0.240 inches and 0.260 inches

Body Length:

Between 1.000 inches and 1.094 inches

Body Width:

Between 0.615 inches and 0.635 inches

Body Height:

Between 0.615 inches and 0.635 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Sleeve

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Maximum Starting Torque:

8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.362 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

Between 0.365 inches and 0.385 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

10.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

Between 295.0 and 305.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

C all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0