## NSN 5905-01-365-6307

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-365-6307

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -300.0/+300.0  Electrical Resistance: 60.000 kilohms  Resistance Tolerance In Percent: -10.000/+10.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 1.370 inches  Body Diameter: 0.345 inches  Body Length: 3.185 inches  Power Dissipation Rating In Watts: |
|--|
| Resistance Tolerance In Percent: -10.000/+10.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.345 inches Body Length: 3.185 inches Power Dissipation Rating In Watts:   |
| Resistance Tolerance In Percent: -10.000/+10.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 1.370 inches  Body Diameter: 0.345 inches  Body Length: 3.185 inches  Power Dissipation Rating In Watts:   |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.345 inches Body Length: 3.185 inches Power Dissipation Rating In Watts:  |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: 1.370 inches  Body Diameter: 0.345 inches  Body Length: 3.185 inches  Power Dissipation Rating In Watts:   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.345 inches Body Length: 3.185 inches Power Dissipation Rating In Watts:   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.345 inches Body Length: 3.185 inches Power Dissipation Rating In Watts:  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.345 inches Body Length: 3.185 inches Power Dissipation Rating In Watts:  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.345 inches Body Length: 3.185 inches Power Dissipation Rating In Watts:  |
| -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.345 inches Body Length: 3.185 inches Power Dissipation Rating In Watts:   |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.345 inches Body Length: 3.185 inches Power Dissipation Rating In Watts:  |
| Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Terminal Length:  1.370 inches  Body Diameter:  0.345 inches  Body Length:  3.185 inches  Power Dissipation Rating In Watts:   |
| Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.345 inches Body Length: 3.185 inches Power Dissipation Rating In Watts:   |
| Wire lead  Reliability Indicator: Not established  Terminal Length: 1.370 inches  Body Diameter: 0.345 inches  Body Length: 3.185 inches  Power Dissipation Rating In Watts:   |
| Reliability Indicator: Not established  Terminal Length: 1.370 inches  Body Diameter: 0.345 inches  Body Length: 3.185 inches  Power Dissipation Rating In Watts:  |
| Not established  Terminal Length: 1.370 inches  Body Diameter: 0.345 inches  Body Length: 3.185 inches  Power Dissipation Rating In Watts:   |
| Terminal Length:  1.370 inches  Body Diameter:  0.345 inches  Body Length:  3.185 inches  Power Dissipation Rating In Watts:   |
| 1.370 inches  Body Diameter: 0.345 inches  Body Length: 3.185 inches  Power Dissipation Rating In Watts:   |
| Body Diameter:  0.345 inches  Body Length:  3.185 inches  Power Dissipation Rating In Watts:   |
| 0.345 inches  Body Length: 3.185 inches  Power Dissipation Rating In Watts:  |
| Body Length: 3.185 inches Power Dissipation Rating In Watts:   |
| 3.185 inches  Power Dissipation Rating In Watts:   |
| Power Dissipation Rating In Watts:   |
|  |
|  |
| 7.500 free air   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A001a0   |
|  |