## NSN 5905-01-365-6311

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-365-6311 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** Between 0.731 inches and 0.843 inches **Mounting Bushing Length:** Between 0.296 inches and 0.328 inches **Body Length:** Between 0.710 inches and 0.790 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 3585.0 and 3615.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 1.50 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

## NSN 5905-01-365-6311

Precision Nonwire Wound Variable Resistor - Page 2 of 2



| Features Provided:  |
|---|
| Humidity proof  |
| Electrical Resistance Per Section:  |
| 1.0 kilohms single section  |
| Rotary Actuator Travel In Angular Deg:                                      |
| Between 3585.0 and 3615.0   |
| Function Conformity Tolerance Per Section:                                  |
| -0.25/+0.25 single section  |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 105.0 single section  |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:   |
| -40.0/+40.0 single section  |
| Power Dissipation Rating Per Section In Watts:                              |
| 5.0 free air single section   |
| Function Conformity Per Section:  |
| Single section independent linearity  |
| Resistance Tolerance Per Section In Percent:                                |
| -10.0/+10.0 single section  |
| Actuator Travel Control Feature:  |
| Stops   |
| Function Characteristic Per Section:  |
| Single section linear   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |
| 25.0 single section   |
| Terminal Type And Quantity:   |
| 3 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A002a0  |
|   |
|   |