NSN 5905-01-366-5965

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-01-366-5965



Body Style: Rectangular bushing mounted **Reliability Indicator:** Not established **Terminal Length:** 0.500 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** Between 0.609 inches and 0.641 inches **Body Width:** Between 0.610 inches and 0.640 inches **Body Height:** Between 0.610 inches and 0.640 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 234.0 and 246.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 1.50 inch-ounces **Maximum Stop Torque:** 64.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.195 inches and 0.205 inches **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef

NSN 5905-01-366-5965

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing
Center To Center Distance Between Terminal Rows:
Between 0.195 inches and 0.205 inches
Features Provided:
Humidity proof
Electrical Resistance Per Section:
500.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 295.0 and 305.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.195 inches and 0.205 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0/+150.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
M single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0