

View Online at <https://aerobasegroup.com/nsn/5905-01-367-9247>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 1.8740 inches and 1.8760 inches

**Pilot Length:**

Between 0.0570 inches and 0.0670 inches

**Undercut Diameter:**

2.031 inches

**Undercut Width:**

0.0730 inches

**Body Diameter:**

2.250 inches

**Shaft Diameter:**

Between 0.2494 inches and 0.2500 inches

**Shaft Length:**

Between 0.844 inches and 0.906 inches

**Body Length:**

1.312 inches

**Mounting Lip Diameter:**

Between 1.9900 inches and 2.0050 inches

**Mounting Lip Depth:**

Between 0.0880 inches and 0.0980 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 348.0 and 352.0

**Maximum Starting Torque:**

1.00 inch-ounces

**Maximum Running Torque:**

1.00 inch-ounces

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.002 inches

**Pilot Diameter Runout:**

0.001 inches

**Shaft Radial Play:**

0.002 inches

**Mechanical Backlash In Deg Angular Rotation:**

0.1

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.10/+0.10 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-700.0/+700.0 single section

**Power Dissipation Rating Per Section In Watts:**

4.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Test Data Document:**

81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:**

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0