NSN 5905-01-368-6769

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-368-6769
Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Terminal Length:
Between 0.484 inches and 0.516 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.375 inches
Body Length:
Between 0.587 inches and 0.649 inches
Body Width:
Between 0.609 inches and 0.641 inches
Body Height:
Between 0.609 inches and 0.641 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Maximum Stop Torque:
64.00 inch-ounces
Nonturn Device Location:
At 9 oclock

Nonturn Device Radius:

Between 0.289 inches and 0.321 inches

Center To Center Distance Between Terminals:

Between 0.219 inches and 0.251 inches

Fragility Factor:

Moderately rugged

NSN 5905-01-368-6769

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing
Center To Center Distance Between Terminal Rows:
Between 0.190 inches and 0.210 inches
Features Provided:
Humidity proof
Electrical Resistance Per Section:
2.5 megohms single section
Rotary Actuator Travel In Angular Deg:
Between 295.0 and 305.0
Center To Center Distance Between Center Terminal And Outside Terminal:
Between 0.190 inches and 0.210 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A002a0