NSN 5905-01-368-7307

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-368-7307
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
4.990 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
14
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.250 inches and 0.350 inches
Body Length:
0.305 inches
Body Width:
Between 0.365 inches and 0.385 inches
Body Height:
0.075 inches
Schematic Diagram Designator:
Ladder network
Power Dissipation Rating In Watts:
0.325 total network
Terminal Width:
Between 0.003 inches and 0.006 inches
Identical Value Resistor Quantity:
13 each resistor
Style Designator:
Flat pack
Test Data Document:
91240 mil r 92401 enceification (includes angineering type bulleting, breehurge, etc., that reflect enceification type data in angification

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-83401/3 government specification

NSN 5905-01-368-7307

Film Fixed Resistor Network - Page 2 of 2



		fe:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0