## NSN 5905-01-370-1122

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-370-1122

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -0.6/+0.6 Electrical Resistance: 114.000 ohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+70.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.875 inches and 1.125 inches Body Length: Between 0.415 inches and 0.455 inches Body Width: Between 0.410 inches and 0.450 inches Body Height: Between 0.165 inches and 0.205 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A001a0	
Electrical Resistance:  114.000 ohms  Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+70.0  Inclosure Method: Encased  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: Between 0.875 inches and 1.125 inches  Body Length: Between 0.415 inches and 0.455 inches  Body Width: Between 0.410 inches and 0.450 inches  Body Height: Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Terminals one edge  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
114.000 ohms  Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+70.0  Inclosure Method: Encased  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: Between 0.875 inches and 1.125 inches  Body Length: Between 0.415 inches and 0.455 inches  Body Width: Between 0.410 inches and 0.450 inches  Body Height: Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Terminals one edge  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Fiig:	-0.6/+0.6
Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+70.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.875 inches and 1.125 inches Body Length: Between 0.415 inches and 0.455 inches Body Width: Between 0.410 inches and 0.450 inches Body Height: Between 0.165 inches and 0.205 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Electrical Resistance:
-0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+70.0  Inclosure Method: Encased  Terminal Type: Wire lead Reliability Indicator: Not established  Terminal Length: Between 0.875 inches and 1.125 inches Body Length: Between 0.415 inches and 0.455 inches Body Width: Between 0.410 inches and 0.450 inches Body Height: Between 0.165 inches and 0.205 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	114.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+70.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.875 inches and 1.125 inches Body Length: Between 0.415 inches and 0.455 inches Body Width: Between 0.410 inches and 0.450 inches Body Height: Between 0.165 inches and 0.205 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -20.0/+70.0  Inclosure Method: Encased  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: Between 0.875 inches and 1.125 inches  Body Length: Between 0.415 inches and 0.455 inches  Body Width: Between 0.410 inches and 0.450 inches  Body Height: Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Terminals one edge  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fiig:	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  125.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+70.0  Inclosure Method: Encased  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: Between 0.875 inches and 1.125 inches  Body Length: Between 0.415 inches and 0.455 inches  Body Width: Between 0.410 inches and 0.450 inches  Body Height: Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Terminals one edge  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+70.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.875 inches and 1.125 inches Body Length: Between 0.415 inches and 0.455 inches Body Width: Between 0.410 inches and 0.450 inches Body Height: Between 0.165 inches and 0.205 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -20.0/+70.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.875 inches and 1.125 inches Body Length: Between 0.415 inches and 0.455 inches Body Width: Between 0.410 inches and 0.450 inches Body Height: Between 0.165 inches and 0.205 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
-20.0/+70.0 Inclosure Method: Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.875 inches and 1.125 inches Body Length: Between 0.415 inches and 0.455 inches Body Width: Between 0.410 inches and 0.450 inches Body Height: Between 0.165 inches and 0.205 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	125.0
Inclosure Method: Encased  Terminal Type: Wire lead  Reliability Indicator: Not established  Terminal Length: Between 0.875 inches and 1.125 inches  Body Length: Between 0.415 inches and 0.455 inches  Body Width: Between 0.410 inches and 0.450 inches  Body Height: Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Terminals one edge  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encased Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.875 inches and 1.125 inches Body Length: Between 0.415 inches and 0.455 inches Body Width: Between 0.410 inches and 0.450 inches Body Height: Between 0.165 inches and 0.205 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-20.0/+70.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 0.875 inches and 1.125 inches Body Length: Between 0.415 inches and 0.455 inches Body Width: Between 0.410 inches and 0.450 inches Body Height: Between 0.165 inches and 0.205 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Terminal Length:  Between 0.875 inches and 1.125 inches  Body Length:  Between 0.415 inches and 0.455 inches  Body Width:  Between 0.410 inches and 0.450 inches  Body Height:  Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Terminals one edge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Encased
Reliability Indicator: Not established  Terminal Length: Between 0.875 inches and 1.125 inches  Body Length: Between 0.415 inches and 0.455 inches  Body Width: Between 0.410 inches and 0.450 inches  Body Height: Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Terminals one edge  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Terminal Type:
Not established  Terminal Length: Between 0.875 inches and 1.125 inches  Body Length: Between 0.415 inches and 0.455 inches  Body Width: Between 0.410 inches and 0.450 inches  Body Height: Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Terminals one edge  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Wire lead
Terminal Length: Between 0.875 inches and 1.125 inches Body Length: Between 0.415 inches and 0.455 inches Body Width: Between 0.410 inches and 0.450 inches Body Height: Between 0.165 inches and 0.205 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Reliability Indicator:
Between 0.875 inches and 1.125 inches  Body Length:  Between 0.415 inches and 0.455 inches  Body Width:  Between 0.410 inches and 0.450 inches  Body Height:  Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Terminals one edge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Not established
Body Length:  Between 0.415 inches and 0.455 inches  Body Width:  Between 0.410 inches and 0.450 inches  Body Height:  Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Terminals one edge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Terminal Length:
Between 0.415 inches and 0.455 inches  Body Width:  Between 0.410 inches and 0.450 inches  Body Height:  Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Terminals one edge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Between 0.875 inches and 1.125 inches
Body Width:  Between 0.410 inches and 0.450 inches  Body Height:  Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Terminals one edge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Length:
Between 0.410 inches and 0.450 inches  Body Height: Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts: 0.100 free air  Style Designator: Terminals one edge  Shelf Life: N/a  Unit Of Measure:  Demilitarization: No  Fiig:	Between 0.415 inches and 0.455 inches
Body Height:  Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Terminals one edge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Width:
Between 0.165 inches and 0.205 inches  Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Terminals one edge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Between 0.410 inches and 0.450 inches
Power Dissipation Rating In Watts:  0.100 free air  Style Designator:  Terminals one edge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Body Height:
0.100 free air  Style Designator:  Terminals one edge  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	Between 0.165 inches and 0.205 inches
Style Designator: Terminals one edge Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Terminals one edge  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.100 free air
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Terminals one edge
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
	Fiig: