

View Online at <https://aerobasegroup.com/nsn/5905-01-373-2999>

**Section Quantity:**

1

**Body Style:**

Rectangular w/bushing/holes/slots

**Reliability Indicator:**

Not established

**Mounting Hole Diameter:**

Between 0.088 inches and 0.098 inches

**Mounting Bushing Length:**

Between 0.235 inches and 0.241 inches

**Body Length:**

Between 1.240 inches and 1.260 inches

**Body Width:**

Between 0.295 inches and 0.305 inches

**Body Height:**

Between 0.395 inches and 0.405 inches

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 8280.0 and 9720.0

**Maximum Starting Torque:**

8.00 inch-ounces

**Maximum Running Torque:**

8.00 inch-ounces

**Fragility Factor:**

Moderately rugged

**Lateral Distance Between Mounting Hole Centers:**

Between 0.990 inches and 1.010 inches

**Screw Thread Diameter:**

0.190 inches

**Screw Thread Series Designator:**

Unc

**Screw Thread Qty Per Inch (tpi):**

32.0

**Mounting Facility Quantity:**

2

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing and unthreaded hole

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

2.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

Between 8280.0 and 9720.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-25.0/+25.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0