

View Online at <https://aerobasegroup.com/nsn/5905-01-373-4822>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

Between 0.844 inches and 0.906 inches

Shaft Diameter:

Between 0.2485 inches and 0.2490 inches

Shaft Length:

2.125 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.547 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

1.063 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

10.0 kilohms all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0