

View Online at <https://aerobasegroup.com/nsn/5905-01-373-6928>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

Between 0.7490 inches and 0.7500 inches

**Pilot Length:**

Between 0.0520 inches and 0.0720 inches

**Undercut Diameter:**

0.7500 inches

**Undercut Width:**

Between 0.0520 inches and 0.0720 inches

**Body Diameter:**

Between 0.870 inches and 0.880 inches

**Shaft Diameter:**

Between 0.120 inches and 0.130 inches

**Shaft Length:**

Between 0.320 inches and 0.380 inches

**Body Length:**

Between 0.450 inches and 0.470 inches

**Mounting Lip Diameter:**

Between 0.8650 inches and 0.8850 inches

**Mounting Lip Depth:**

Between 0.0520 inches and 0.0720 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

0.25 inch-ounces

**Maximum Running Torque:**

0.15 inch-ounces

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Rear end

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0