

View Online at <https://aerobasegroup.com/nsn/5905-01-373-6928>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.7490 inches and 0.7500 inches

Pilot Length:

Between 0.0520 inches and 0.0720 inches

Undercut Diameter:

0.7500 inches

Undercut Width:

Between 0.0520 inches and 0.0720 inches

Body Diameter:

Between 0.870 inches and 0.880 inches

Shaft Diameter:

Between 0.120 inches and 0.130 inches

Shaft Length:

Between 0.320 inches and 0.380 inches

Body Length:

Between 0.450 inches and 0.470 inches

Mounting Lip Diameter:

Between 0.8650 inches and 0.8850 inches

Mounting Lip Depth:

Between 0.0520 inches and 0.0720 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Maximum Starting Torque:

0.25 inch-ounces

Maximum Running Torque:

0.15 inch-ounces

Fragility Factor:

Moderately rugged

Terminal Location:

Rear end

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Electrical Resistance Per Section:

10.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0