Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-376-0723

## Section Quantity:

2

Body Style:

Rectangular bushing mounted

## Reliability Indicator:

Not established

## Shaft Diameter:

0.125 inches

#### Shaft Length:

0.625 inches

## Mounting Bushing Length:

0.250 inches

#### Body Length:

1.025 inches

#### Body Width:

## 0.625 inches

**Body Height:** 

0.625 inches

Shaft Style:

Round

#### Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

240.0

#### Maximum Running Torque:

4.00 inch-ounces

#### **Terminal Location:**

Longitudinally positioned on the circumference

#### Mounting Method:

Standard bushing

# Center To Center Distance Between Terminal Rows:

0.200 inches

# **Electrical Resistance Per Section:**

50.0 kilohms all sections

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 all sections

# Power Dissipation Rating Per Section In Watts:

1.0 free air all sections

# **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 wire loop

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0